

Overview

Plexstar repeaters are optical-electrical-optical (O-E-O) media converter/ transponders for extending the optical fiber distance between two locations that support the "Three R's" for Retiming, Regenerating and Reshaping of the optical signal. In some applications O-E-Os are also used for wavelength conversion from proprietary CWDM/DWDM wavelength to a generic wavelength for example 1310nm/1550nm.

Model:

- POEOCH17: 16 slot repeater chassis with management POEO25G3RS: 2.5G Repeater/Transponder (2 x SFP).
- PLX-1306-15-XD, PLX-1324-15-XD, BLXFP-2.5G.

Specifications

- 3R repeater (Retime, Regenerate, and Reshape).
- Support ITUT prescribed CWDM wavelength (1270nm-1610nm).
- Protocol and optical transmission rate agnostic.
- Modular filter and fan unit that is in-service replaceable.
- Transponders are hot pluggable.

Power:

- AC/DC Redundant and modular power supplies.
- Less than 5W per repeater/transponder .

Physical Dimension:

- 2RU chassis with 17 slots.
- Card: Height 8.5 mm (0.33 inches), Width 13.4 mm (0.53 inches), Depth 56.5 mm (2.22 inches).

Applications

- Gigabit Ethernet Interface
- STM1/STM4/STM16 Optical Interface
- OC3/OC12/OC48 Optical Interface
- SONET, SDH, OTN, FC Optical Interface
- Digital video
- Multimode fiber to single-mode fiber converter
- Dual fiber to single bidirectional fiber communication
- Converts CWDM/DWDM wavelength to a common wavelength
- Network Management function Web, SNMP

Plexstar Line Amplifier Used in a Single Bidirectional Fiber Transmission

